

report-reg- number-of- measure	report-reg-taric-ext
--------------------------------------	----------------------

5 2712209000

6 2811220040

7 2825904030

8 2833298040

9 2903220000

10 2903793020

11 2903998030

12 2905120010

13 2906190040

14 2907120010

15 2909498020

16 2912420000

17 2914199050

18 2914290060

19 2915210010

20 2915240000

21 2915320000

22 2916199530

23 2916399028

24 2917139010

25 2917198040

26 2918220010

27 2918290075

28 2918290080

29 2918300010

30 2920290070

31 2920901070

32 2921290060

33 2921410010

34 2921511910

35 2924190085

37 2926907084

38 2927000085

39 2928009015

40 2929900030

41 2932120000

42 2932190060

43 2932209025

44 2932209030

45 2932209077

46 2932930000

47 2933299085

48 2933399943

49 2933399944

50 2933599539

51 2933698030

52 2933998073

53 2934999051

54 2935909079

55 2935909091

56 2940000020

57 3204110075

58 3204170014

59 3204170030

60 3802900019

61 3804000010

62 3805109000

63 3806100010

64 3808929040

65 3811290055

66 3815909076

67 3824999271

68 3824999277

69 3824999285

70 3824999287

71 3824999289

72 3824999343

73 3824999367

74 3905300000

75 3905999081

76 3907400025

77 3911901910

78 3912110020

79 3913100010

80 3913900087

81 3920510050

82 3921140020

83 5505101010

84 5906999020

85 6902900010

86 7019120006
86 7019120026
87 7019400070

87 7019520030

88 7019520010
89 7202499010

90 7409110020
90 7410110030
91 7410210055

92 7604291020
93 7604291030
94 7609000020
95 8104110000
96 8104300020
97 8302490091

98 8414900070
99 8481808540

100 8483308020
101 8501402040

101 8501408030

102 8504408220

103 8504408230

104 8526912020

105 8529909275

105 9405403970

106 8543709063

107 8708999775

108 8714109030

109 8714109040

110 8714109060

111 8714911021

111 8714911031

112 9001900080

113 9003110010

113 9003190020

114 9027109020

report-reg-description

#Paraffin wax containing by weight less than 0,75 % of oil#
#Silica filler in the form of granules, with a purity by weight of 97 % or more of silicon dioxide#
#Tungsten trioxide, including blue tungsten oxide (CAS RN 1314-35-8 or CAS RN 39318-18-8)#
#Cesium sulphate (CAS RN 10294-54-9) in solid form or as aqueous solution containing by weight 48 % or more but not more than 52 % of cesium sulphate#
#Trichloroethylene (CAS RN 79-01-6)#
#Bromochloromethane (CAS RN 74-97-5)#
#1,3-Dichlorobenzene (CAS RN 541-73-1)#
#Propan-1-ol (propyl alcohol) (CAS RN 71-23-8)#
#Cyclopropylmethanol (CAS RN 2516-33-8)#
#O-Cresol (CAS RN 95-48-7) having a purity of not less than 98,5 % by weight#
#2,2,2',2'-Tetrakis(hydroxymethyl)-3,3'-oxydipropyl-1-ol (CAS RN 126-58-9)#####
#Ethylvanillin (3-ethoxy-4-hydroxybenzaldehyde) (CAS RN 121-32-4)#
#Calcium acetylacetonate (CAS RN 19372-44-2) for use in the manufacture of stabilisator systems in tablet form#

#Cyclopropyl methyl ketone (CAS RN 765-43-5)#
#Acetic acid (CAS RN 64-19-7) of a purity by weight of 99 % or more#
#Acetic anhydride (CAS RN 108-24-7)#
#Vinyl acetate (CAS RN 108-05-4)#
#Potassium (E,E)-hexa-2,4-dienoate (CAS RN 24634-61-5)#
#2,5-dimethylphenylacetyl chloride (CAS RN 55312-97-5)#
#Dimethyl sebacate (CAS RN 106-79-6)#
#Dodecanedioic acid, of a purity by weight of more than 98,5 % (CAS RN 693-23-2)
o -Acetylsalicylic acid (CAS RN 50-78-2)
#Octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (CAS RN 2082-79-3) with#### a sieve passing fraction at a mesh width of 500 µm of more than 99 % by weight and # a melting point of 49 °C or more, but not more than 54 °C, # ####for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates)#
#Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8)#### with a sieve passing fraction at a mesh width of 250 µm of more than 75 % by weight and at a mesh width of 500 µm of more than 99 % by weight, and # a melting point of 110 °C or more, but not more than 125 °C, # ####for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates)#

#Benzophenone-3,3',4,4'-tetracarboxylic dianhydride (CAS RN 2421-28-5)#
#Tris (2,4-di-tert-butylphenyl)phosphite (CAS RN 31570-04-4)#
#Dimethyl Sulphate (CAS RN 77-78-1)#
#Bis(2-dimethylaminoethyl)(methyl)amine (CAS RN 3030-47-5)#
#Aniline with a purity by weight of 99 % or more (CAS RN 62-53-3)#
o-Phenylenediamine (CAS RN 95-54-5)

#3-Iodoprop-2-ynyl N-butylcarbamate (CAS RN 55406-53-6)#
 #2-Nitro-4(trifluoromethyl)benzonitrile (CAS RN 778-94-9)#
 #C,C'-Azodi(formamide) (CAS RN 123-77-3) with:## # a pH of 6,5 or more but not more than 7,5, and # a semicarbazide (CAS RN 57-56-7) content of not more than 1 500 mg/kg as determined by liquid chromatography mass spectrometry (LC-MS), # decomposition temperature range of 195 °C - 205 °C, # specific gravity 1,64 - 1,66, and # combustion heat 215 - 220 Kcal/mol #
 #Monomethylhydrazine (CAS 60-34-4) in the form of an aqueous solution with a content by weight of monomethylhydrazine of 40 (± 5) %#
 #Nitroguanidine (CAS RN 556-88-7)#
 #2-Furaldehyde (furfuraldehyde)#
 Flurtamone (ISO) (CAS RN 96525-23-4)
 #Decan-5-olide (CAS RN 705-86-2)#
 #Dodecan-5-olide (CAS RN 713-95-1)#
 #Hexan-6-olide (CAS RN 502-44-3)#
 #Piperonal (CAS RN 120-57-0)#
 #Enzalutamide INN (CAS RN 915087-33-1)#
 #2,2,6,6-Tetramethylpiperidin-4-ol (CAS RN 2403-88-5)#
 #Chlorpyrifos (ISO) (CAS RN 2921-88-2)#
 #Ibrutinib (INN) (CAS RN 936563-96-1)#
 #1,3,5-Tris[3-(dimethylamino)propyl]hexahydro-1,3,5-triazine (CAS RN 15875-13-5)#
 #5-(Acetoacetyl amino)benzimidazolone (CAS RN 26576-46-5)#
 #Canagliflozin (INN) (CAS RN 928672-86-0)#
 #4-[[[2-Methoxybenzoyl]amino]sulfonyl]benzoyl chloride (CAS RN 816431-72-8)#
 #2,4,4-Trimethylpentan-2-aminium (3R,5S,E)-7-(4-(4-fluorophenyl)-6-isopropyl-2-(N-methylmethylsulfonamido)pyrimidin-5-yl)-3,5-dihydroxyhept-6-enoate (CAS RN 917805-85-7)#
 D-Xylose (CAS RN 58-86-6)
 #Colourant C.I. Disperse Yellow 54 (CAS RN 7576-65-0) and preparations based thereon with a colourant C.I. Disperse Yellow 54 content of 99 % or more by weight#
 #Preparations based on Colourant C.I. Pigment Red 48:2 (CAS RN 7023-61-2) with a content thereof of 60 % or more by weight#
 #Colourant C.I. Pigment Red 4 (CAS RN 2814-77-9) and preparations based thereon with a colourant C.I. Pigment Red 4 content of 60 % or more by weight#
 #Soda flux calcinated diatomaceous earth#
 Sodium lignosulphonate
 Sulphate turpentine
 #Rosin and resin acids obtained from fresh oleoresins#
 #Preparation containing 38 % or more but not more than 50 % by weight of pyrrhione zinc (INN) (CAS RN 13463-41-7) in an aqueous dispersion#
 #Additives consisting of reaction products of diphenylamine and branched nonenes with:### # by weight more than 28 %, but not more than 35 % of 4-monononyldiphenylamine, and # by weight more than 50 % but not more than 65 % of 4,4'-dinonyldiphenylamine, # by weight a total percentage of 2, 4-dinonyldiphenylamine and 2, 4'-dinonyldiphenylamine of not more than 5 %, # ###used for the manufacture of lubricating oils#
 #Catalyst consisting of titanium dioxide and tungsten trioxide#

#Mixtures containing by weight:### # 60 % or more but not more than 90 % of 2-chloropropene (CAS RN 557-98-2), # 8 % or more but not more than 14 % of (Z)-1-chloropropene (CAS RN 16136-84-8), # 5 % or more but not more than 23 % of 2-chloropropane (CAS RN 75-29-6), # not more than 6 % of 3-chloropropene (CAS RN 107-05-1), and # not more than 1 % of ethyl chloride (CAS RN 75-00-3) #

#Preparation containing by weight:### # 55 % or more but not more than 78 % of dimethyl glutarate, # 10 % or more but not more than 30 % of dimethyl adipate, and # not more than 35 % of dimethyl succinate #

#Mixture of bis [3-(triethoxysilyl)propyl]sulphides (CAS RN 211519-85-6)#

#Acetophenone (CAS RN 98-86-2), with a purity by weight of 60 % or more but not more than 90 %#

#Mixture of tertiary alkyl dimethyl amines containing by weight:### # 60 % or more but not more than 80 % of dodecyl dimethylamine (CAS RN 112-18-5), and # 20 % or more but not more than 30 % of dimethyl(tetradecyl)amine (CAS RN 112-75-4) #

#Solid extract of the residual, insoluble in aliphatic solvents, obtained during the extraction of rosin from wood, having the following characteristics:### # a resin acid content not exceeding 30 % by weight, # an acid number not exceeding 110 # ###and### # a melting point of 100° C or more #

#Mixture of phytosterols, in the form of powder, containing by weight:### # 75 % or more of sterols, # not more than 25 % of stanols # ###for use in the manufacture of stanols/sterols or stanol/sterol esters#

#Poly(vinyl alcohol), whether or not containing unhydrolysed acetate groups#

#Poly(vinyl butyral)(CAS RN 63148-65-2):### # containing by weight 17,5 % or more, but not more than 20 % of hydroxyl groups, and # with a median particle size (D50) of more than 0,6 mm # ### #

#Polymer blend of polycarbonate and poly(methyl methacrylate) with a polycarbonate content of not less than 98,5 % by weight, in the form of pellets or granules, with a luminous transmittance of not less than 88,5 %, measured using a test sample with a thickness of 4 mm at a wavelength of $\lambda = 400$ nm (according to ISO 13468-2)#

#Poly(oxy-1,4-phenylenesulphonyl-1,4-phenyleneoxy-4,4'-biphenylene)#

#Cellulose acetate flakes#

#Sodium alginate, extracted from brown seaweed (CAS RN 9005-38-3)####

#Sodium hyaluronate, non sterile, with:### # a weight average molecular weight (M w) of not more than 900 000, # an endotoxin level of not more than 0,008 Endotoxin units (EU)/mg, # an ethanol content of not more than 1 % by weight, # an isopropanol content of not more than 0,5 % by weight #

#Sheets of polymethylmethacrylate conforming to standards:## # EN 4364 (MIL-P-5425E) and DTD5592A, or # EN 4365 (MIL-P-8184) and DTD5592A #

#Cellular block of regenerated cellulose, impregnated with water containing magnesium chloride and quaternary ammonium compounds, measuring 100 cm (± 10 cm) x 100 cm (± 10 cm) x 40 cm (± 5 cm)#

#Waste of synthetic fibres (including noils, yarn waste, and garnetted stock) of nylon or other polyamides (PA6 and PA66)#

#Woven and laminated rubberised textile fabric with the following characteristics:### # with three layers, # one outer layer consists of acrylic fabric, # the other outer layer consists of polyester fabric, # the middle layer consists of chlorobutyl rubber, # the middle layer has a weight of 486 g/m² or more but not more than 569 g/m², # the textile fabric has a total weight of 952 g/m² or more but not more than 1159 g/m², # the textile fabric has a total thickness of 0.8 mm or more but not more than 4 mm, # ###used for the manufacture of the retractable roof of motor vehicles#

#Refractory bricks with## # an edge length of more than 300 mm and # a TiO₂ content of not more than 1 % by weight and # a Al₂O₃ content of not more than 0.4 % by weight and # a change in volume of less than 9 % at 1700° C #

#S glass stratifils (rovings):### # composed of continuous glass filaments of 9 μm ($\pm 0,5 \mu\text{m}$), # measuring 200 tex or more but not more than 680 tex, # not containing any calcium oxide, and # with a breaking strength of more than 3 550 Mpa determined by ASTM D2343-09 # ###for use in the manufacture of aeronautics#

#S glass stratifils (rovings):### # composed of continuous glass filaments of 9 μm ($\pm 0,5 \mu\text{m}$), # measuring 200 tex or more but not more than 680 tex, # not containing any calcium oxide, and # with a breaking strength of more than 3 550 Mpa determined by ASTM D2343-09 # ###for use in the manufacture of aeronautics#

#E-fibre glass fabrics:### # having a weight of 20 g/m^2 or more, but not more than 214 g/m^2 , # impregnated with silane, # in rolls, # having a humidity content by weight of 0,13 % or less, and # having not more than 3 hollow fibres out of 100 000 fibres, # ###for the exclusive use in the manufacture of prepregs and copper clad laminates#

#E-fibre glass fabrics:### # having a weight of 20 g/m^2 or more, but not more than 214 g/m^2 , # impregnated with silane, # in rolls, # having a humidity content by weight of 0,13 % or less, and # having not more than 3 hollow fibres out of 100 000 fibres, # ###for the exclusive use in the manufacture of prepregs and copper clad laminates#

#Glass web woven from glass fibre coated in plastic, of a weight of 120 g/m^2 ($\pm 10 \text{ g}/\text{m}^2$), of a type used in rolling insect screens with fixed frames#

#Ferro-chromium containing 1,5 % or more but not more than 4 % by weight of carbon and not more than 70 % of chromium#

#Refined copper foil and strips, electrolytically coated#

#Refined copper foil and strips, electrolytically coated#

#Plates:### # consisting of at least one layer of fibreglass fabric impregnated with epoxide resin, # covered on one or both sides with copper foil with a thickness of not more than 0,15 mm, # with a dielectric constant (DK) of less than 5,4 at 1 MHz, as measured according to IPC-TM-650 2.5.5.2, # with a loss tangent of less than 0,035 at 1 MHz, as measured according to IPC-TM-650 2.5.5.2, # with a comparative tracking index (CTI) of 600 or more #

#Aluminium alloy rods with a diameter of 200 mm or more, but not exceeding 300 mm#

#Aluminium alloy rods with a diameter of 300,1 mm or more, but not more than 533,4 mm#

#Aluminium tube or pipe fittings for affixing to radiators of motor bikes#

#Unwrought magnesium, containing at least 99,8 % by weight of magnesium#

#Magnesium powder:### # of purity by weight of 98 % or more, but not more than 99,5 % # with a particle size of 0,2 mm or more but not more than 0,8 mm #

#Aluminium telescopic handle for use in the manufacture of luggage#

#Aluminium alloy compressor wheel with:### # a diameter of 20 mm or more, but not more than 130 mm, and # a weight of 5 g or more, but not more than 800 g # ###for use in the manufacture of combustion engines#

#Exhaust valve for use in the manufacture of motorcycle exhaust gas systems#

#Wave slide bearing for axial applications, of FeP01 steel (according to EN 10130-1991) with a sliding layer of porous sinter bronze and poly(tetrafluoroethylene), suitable for installation into motor bike suspension units#

#Electric AC commutator motor, single-phase, with an output of 250 W or more, an input power of 700 W or more but not more than 2 700 W, an external diameter of more than 120 mm ($\pm 0,2 \text{ mm}$) but not more than 135 mm ($\pm 0,2 \text{ mm}$), a rated speed of more than 30 000 rpm but not more than 50 000 rpm, equipped with air-inducting ventilator, for use in the manufacture of vacuum cleaners#

#Electric AC commutator motor, single-phase, with an output of 250 W or more, an input power of 700 W or more but not more than 2 700 W, an external diameter of more than 120 mm ($\pm 0,2$ mm) but not more than 135 mm ($\pm 0,2$ mm), a rated speed of more than 30 000 rpm but not more than 50 000 rpm, equipped with air-inducting ventilator, for use in the manufacture of vacuum cleaners#

#Electric rectifier, with a capacity of not more than 1 kVA, for use in the manufacture of appliances falling within subheading 8509 80 and heading 8510#

#Power supply boards for use in the manufacture of goods falling under heading 8521 and 8528#

#Assembly for GPS system having a position determination function, without display, and a weight of not more than 2 500 g#

#Printed circuit board with LED diodes:### # whether or not equipped with prisms/lens, and # whether or not fitted with connector(s) # ####for the manufacture of backlight units for goods of heading 8528##### #

#Printed circuit board with LED diodes:### # whether or not equipped with prisms/lens, and # whether or not fitted with connector(s) # ####for the manufacture of backlight units for goods of heading 8528##### #

#Voltage controlled frequency generator, consisting of active and passive elements mounted on a printed circuit, contained in a housing with dimensions of not more than 30 mm x 30 mm#

#Aluminium alloy support bracket, with mounting holes, whether or not with fixation nuts, for indirect connection of the gearbox to the car body for use in the manufacture of goods of Chapter 87#

#Axle clamps, housings, fork bridges and clamping pieces, of aluminium alloy of a kind used for motor bikes#

#Pistons for steering dampers of sintered steel according to standard ISO P2054 of a kind used for motor bikes#

#Pistons for suspension systems, having a diameter of not more than 55 mm, of sintered steel#

#Bicycle frame, constructed from carbon fibres and artificial resin, painted, lacquered and/or polished, for use in the manufacture of bicycles#

#Bicycle frame, constructed from carbon fibres and artificial resin, painted, lacquered and/or polished, for use in the manufacture of bicycles#

#Unmounted glass lenses, prisms and cemented elements for use in the manufacture or repair of goods of CN codes 9002, 9005, 9013 10 and 9015#

#Spectacle frames of plastic or base metal for use in the manufacture of corrective glasses#

#Spectacle frames of plastic or base metal for use in the manufacture of corrective glasses#

#Lambda sensors for permanent incorporation into motor cycle exhaust systems#