

ANNEX I

CN code	TARIC	Description
ex 2906 11 00	10	Levomenthol (INN) (CAS RN 2216-51-5)
ex 2915 90 70	85	Ethyl trifluoroacetate (CAS RN 383-63-1)
ex 2916 39 90	28	2,5-dimethylphenylacetyl chloride (CAS RN 55312-97-5)
ex 2921 59 90	80	4,4'-Methanediyl dianiline (CAS RN 101-77-9) in form of granules, for use in the manufacture of prepolymers (2)
ex 2933 39 99	66	Fluazinan (ISO) (CAS RN 79622-59-6), with a purity by weight of 98,5 % or more
ex 7409 19 00	20	Plates or sheets consisting of — a layer of a silicon nitride ceramic with a thickness of 0,32 mm ($\pm 0,1$ mm) or more but not more than 1,0 ($\pm 0,1$ mm) mm, — covered on both sides with a foil of refined copper with a thickness of 0,8 mm ($\pm 0,1$ mm) and — on one side partially covered with a coating of silver
ex 7607 11 90	83	Aluminium and magnesium alloy strip or foil: — of an alloy conforming to standards 5182-H19 or 5052-H19, — in rolls with an outside diameter of not more than 1 350 mm , — of a thickness (tolerance - 0,006 mm) of 0,15 mm, 0,16 mm, 0,18 mm or 0,20 mm, — a width (tolerance $\pm 0,3$ mm) of 12,5 mm, 15,0 mm, 16,0 mm, 25,0 mm, 35,0 mm, 50,0 mm or 356 mm, — a camber tolerance of not more than 0,5 mm/750 mm, — a flatness measurement of I-unit ± 5 , — a tensile strength of more than (5182-H19) 365MPa or (5052-H19) 320MPa, and — an elongation at break of more than (5182-H19) 3 % or (5052-H19) 2,5 % for use in the manufacture of slats for blinds (2)

ANNEX II

CN code	TARIC	Description
ex 2905 12 00	10	Propan-1-ol (propyl alcohol) (CAS RN 71-23-8)
2912 42 00		Ethylvanillin (3-ethoxy-4-hydroxybenzaldehyde) (CAS RN 121-32-4)
ex 2918 29 00	80	Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8) — with a sieve passing fraction at a mesh width of 250 µm of more than 75 % by weight and at a mesh width of 500 µm of more than 99 % by weight, and — a melting point of 110 °C or more, but not more than 125 °C, for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates) (2)
ex 2920 90 10	70	Dimethyl Sulphate (CAS RN 77-78-1)
ex 2921 41 00	10	Aniline with a purity by weight of 99 % or more (CAS RN 62-53-3)
ex 2932 20 90	25	Decan-5-olide (CAS RN 705-86-2)
ex 2932 20 90	30	Dodecan-5-olide (CAS RN 713-95-1)
ex 3204 17 00	14	Preparations based on Colourant C.I. Pigment Red 48:2 (CAS RN 7023-61-2) with a content thereof of 60 % or more but less than 85 % by weight
ex 3811 29 00	55	Additives consisting of reaction products of diphenylamine and branched nonenes with: — by weight more than 28 %, but not more than 55 % of 4-monononyldiphenylamine, and — by weight more than 45 % but not more than 65 % of 4,4'-dinonyldiphenylamine, — by weight not more than 5 % of 2, 4-dinonyldiphenylamine and 2, 4'-dinonyldiphenylamine, used for the manufacture of lubricating oils (2)
ex 5906 99 90	20	Woven and laminated rubberised textile fabric with the following characteristics: — with three layers, — one outer layer consists of acrylic fabric, — the other outer layer consists of polyester fabric, — the middle layer consists of chlorobutyl rubber, — the middle layer has a weight of 452 g/m ² or more but not more than 569 g/m ² , — the textile fabric has a total weight of 952 g/m ² or more but not more than 1159 g/m ² , — the textile fabric has a total thickness of 0,8 mm or more but not more than 4 mm, used for the manufacture of the retractable roof of motor vehicles (2)
ex 8504 40 82	30	Power supply boards for use in the manufacture of goods falling under heading 8521 and 8528 (2)